



# Xitanium LED downlight and spotlight drivers

## XITANIUM 36W WH 0.3-1A 54V TD/IS CL 230V

Xitanium LED drivers are leading the way in terms of reliability

### Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	1050 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	37 W
Output Power (Min)	11 W
Output Current (Min)	300 mA
Output Voltage (Max)	54 V
Output Voltage (Min)	24 V
Protection class IEC	Safety class I/II
System characteristics	
Central DC Operation	Yes
YellowDot ready	Yes
Temperature	
T-Case Lifetime (Max)	75 °C

T-Case Maximum (Max)	85 °C
Controls and Dimming	
Dimmable	DALI
Dimming Range	100-1 %
Mechanical and Housing	
Product Length	200 mm
Housing	WH Independent
Overall length	200 mm
Overall width	75 mm
Overall height	32 mm
Dimensions (Height x Width x Depth)	32 x 75 x 200 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.204 kg
Approval and Application	
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance

## Xtanium LED downlight and spotlight drivers

<b>Output Current Set Options</b>	DALI, NFC
<b>Product Data</b>	
<b>Order product name</b>	XITANIUM 36W WH 0.3-1A 54V TD/IS CL 230V
<b>Full product name</b>	XITANIUM 36W WH 0.3-1A 54V TD/IS CL 230V
<b>Full product code</b>	871869959373500
<b>Order code</b>	929001649706

<b>Material Nr. (12NC)</b>	929001649706
<b>Numerator - Quantity Per Pack</b>	1
<b>EAN/UPC - Product/Case</b>	8718699593735
<b>Numerator - Packs per outer box</b>	20
<b>EAN/UPC - Case</b>	8718699593742

