



# Xitanium LED downlight and spotlight drivers

## Xitanium 20W R 0.15-0.5A 54V TD/I

Xitanium LED drivers are leading the way in terms of reliability

### Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	500 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	20 W
Output Power (Min)	6.5 W
Output Current (Min)	150 mA
Output Voltage (Max)	54 V
Output Voltage (Min)	24 V
Protection class IEC	Safety class I/II
System characteristics	
Central DC Operation	Yes
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	60 °C

T-Case Maximum (Max)	70 °C
Controls and Dimming	
Dimmable	DALI
Control Interface	DALI TD
Mechanical and Housing	
Product Length	127 mm
Overall length	127.6 mm
Overall width	74 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 74 x 128 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.150 kg
Approval and Application	
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	LEDSet

## Xtanium LED downlight and spotlight drivers

### Product Data

Order product name	Xtanium 20W R 0.15-0.5A 54V TD/1
Full product name	Xtanium 20W R 0.15-0.5A 54V TD/1
Full product code	871951425106900
Order code	929002801106
Material Nr. (12NC)	929002801106

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514251069
Numerator - Packs per outer box	18
EAN/UPC - Case	8719514251076

